

Front Derailleur MTB

Model No.	FDMS66	FDMS28	FDMS20	FDM966	FDM924	FDM920	FDM500	FDM300
Rear Compatibility	10-Speed	10-Speed	10-Speed	9-Speed	9-Speed	9-Speed	8 / 7-Speed	8 / 7-Speed
Chaining Compatibility	Double	Triple	Triple	Double	Triple	Triple	Triple	Triple
Action	Top Swing	Top Swing	Top Swing	Top Swing	Top Swing	Top Swing	Top Swing	Top Swing
Top Gear Teeth	34~38T	48T	40T	34~38T	44T / 48T	40T	42T	42T / 48T
Top-Low Max. Capacity	14T	22T	18T	14T	22T	18T	18T	20T
Top-Middle Min. Capacity	X	12T	10T	X	12T	10T	8T	10T
Clamp Diameter	(2) E-Type / (L) 34.9 / (M) 31.8* / (S) 28.6*mm			(2) E-Type / (L) 34.9 / (M) 31.8* / (S) 28.6*mm			(L) 34.9 / (M) 31.8* / (S) 28.6*mm	
Cable Routing	(D) Dual Pull			(D) Dual Pull			(D) Dual Pull	
Chain Stay Angle	66~69°			66~69°			66~69°	
Chain Guide	Matt Chrome Plated			Chrome Plated			Chrome Plated	
Base Bracket Material	Aluminum			Aluminum			Aluminum	
Clamp Material	Aluminum			Aluminum			Aluminum	
Clamp Bolt	Stainless Steel			Stainless Steel			SCM435 Chromoly	
Cable Fixing Bolt	Stainless Steel			Stainless Steel			SCM435 Chromoly	
Average Weight	136g (L)	149g (L)	145g (L)	136g (L)	149g (L)	145g (L)	146g (L)	143g (L)

* With multi clamp band inserts which convert 34.9mm to 31.8mm or 28.6mm

Front Derailleur MTB

Model No.	FDM2A	FDM2S	FDM05	FDM06
Rear Compatibility	7 / 6-Speed	7 / 6-Speed	7 / 6 / 5-Speed	6 / 5-Speed
Chainring Compatibility	Triple	Triple	Triple Friction	Double Friction
Action	Down Swing	Down Swing	Down Swing	Down Swing
Top Gear Teeth	48T	42T	48T	48T
Top-Low Max. Capacity	20T	18T	20T	10T
Top-Middle Min. Capacity	10T	8T	10T	X
Clamp Diameter	(M) 31.8 / (S) 28.6mm*		(M) 31.8 / (S) 28.6mm	(S) 28.6mm
Cable Routing	(T) Top Pull / (B) Bottom Pull		(B) Bottom Pull	(B) Bottom Pull
Chain Stay Angle	66~69°		66~69°	66~69°
Average Weight	154g (M)	144g (M)	148g	142g

* Optional multi clamp band inserts which convert 31.8mm to 28.6mm