

ST Trigger Shifters

Model No.		STMX33			STMS33			STMS13		
		RE	L2	L3	RT	L2	L3	RT	L2	L3
Shift Lever	Side and Speed	Right 11-Spd	Left 2-Spd	Left 3-Spd	Right 10-Spd	Left 2-Spd	Left 3-Spd	Right 10-Spd	Left 2-Spd	Left 3-Spd
	Gear Display	Podium Top			Podium Top			Podium Top		
	Shifting Operation	Push-Pull			Push-Pull			Push-Pull		
	Cable Adjuster	●			●			●		
	Multiple Shifts (Max.)	4	1	1	4	1	1	4	1	1
	Large Lever	Aluminum			Aluminum			Engineering Polymers		
	Small Lever	Engineering Polymers			Engineering Polymers			Engineering Polymers		
	Cable Type	Slick-Stainless			Slick-Stainless			Slick-Galvanized		
	Cable Length	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm
	Casing Compatibility	SP			SP			SP		
Brake Lever	Compatible Brake	V-Brake / Mechanical Disc			V-Brake / Mechanical Disc			V-Brake / Mechanical Disc		
	Lever Length	2-Finger			2-Finger			2-Finger		
	Lever Material	Forged Aluminum / Anodized Black			Forged Aluminum / Anodized Black			Aluminum / Painted Black		
	Bracket Material	Aluminum / Painted Black			Aluminum / Painted Black			Aluminum / Painted Black		
	Cable Adjuster	Aluminum / Anodized			Aluminum / Anodized			Aluminum / Anodized		
	Reach Adjuster	Steel / Ruspert			Steel / Ruspert			Steel / Ruspert		
	Bracket Bolt	Steel / Ruspert			Steel / Ruspert			Steel / Ruspert		
Clamp Screw	Stainless Steel			Stainless Steel			SCM435 Chromoly			
Finish	Black			Black			Black			
Average Weight	211g	212g	212g	211g	212g	212g	214g	215g	215g	

* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

ST Trigger Shifters

Model No.		STM933			STM906			STM906J(Juvenile)
		R9	L2	L3	R9	L2	L3	R9
Shift Lever	Side and Speed	Right 9-Spd	Left 2-Spd	Left 3-Spd	Right 9-Spd	Left 2-Spd	Left 3-Spd	Right 9-Spd
	Gear Display	Podium Top			Podium Top			Podium Top
	Dual Release Function	Push-Pull			Push-Pull			Push-Pull
	Cable Adjuster	●			●			●
	Multiple Shifts (Max.)	6	1	1	6	1	1	6
	Large Lever	Aluminum			Engineering Polymers			Engineering Polymers
	Small Lever	Engineering Polymers			Engineering Polymers			Engineering Polymers
	Cable Type	Slick-Stainless			Slick-Galvanized			Slick-Galvanized
	Cable Length	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm	2,100mm
	Casing Compatibility	SP			SP			SP
Brake Lever	Compatible Brake	V-Brake / Mechanical Disc			V-Brake / Mechanical Disc			V-Brake / Mechanical Disc
	Lever Length	2-Finger			2-Finger			2-Finger / Juvenile
	Lever Material	Forged Aluminum / Anodized Black			Aluminum / Painted Black			Aluminum / Painted Black
	Bracket Material	Aluminum / Painted Black			Aluminum / Painted Black			Aluminum / Painted Black
	Cable Adjuster	Aluminum / Anodized			Aluminum / Anodized			Aluminum / Anodized
	Reach Adjuster	Steel / Ruspert			Steel / Ruspert			Steel / Ruspert
	Bracket Bolt	Steel / Ruspert			Steel / Ruspert			Steel / Ruspert
	Clamp Screw	Stainless Steel			SCM435 Chromoly			SCM435 Chromoly
Finish	Black			Black			Black	
Average Weight	211g	212g	212g	219g	220g	220g	196g	

* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

ST Trigger Shifters

Model No.		STM406			STM406J (Juvenile)
		R8	R7	L3	R8
Shift Lever	Side and Speed	Right 8-Spd	Right 7-Spd	Left 3-Spd	Right 8-Spd
	Gear Display	Podium Top			Podium Top
	Dual Release Function	Push-Pull			Push-Pull
	Cable Adjuster	●			●
	Multiple Shifts (Max.)	5	5	1	5
	Large Lever	Engineering Polymers			Engineering Polymers
	Small Lever	Engineering Polymers			Engineering Polymers
	Cable Type	Slick-Galvanized			Slick-Galvanized
	Cable Length	2,100mm	2,100mm	1,700mm	2,100mm
	Casing Compatibility	SP	2SP & ↑	2SP & ↑	SP
Brake Lever	Compatible Brake	V-Brake / Mechanical Disc			V-Brake / Mechanical Disc
	Lever Length	2-Finger			2-Finger / Juvenile
	Lever Material	Aluminum / Natural Silver			Aluminum / Natural Silver
	Bracket Material	Aluminum / Painted Black			Aluminum / Painted Black
	Cable Adjuster	Aluminum / Natural Silver			Aluminum / Natural Silver
	Reach Adjuster	Steel / Ruspert			Steel / Ruspert
	Bracket Bolt	Steel / Ruspert			Steel / Ruspert
	Clamp Screw	SCM435 Chromoly			SCM435 Chromoly
Finish	(B) Black / (A) Alloy Silver + Black			(A) Alloy Silver + Black	
Average Weight	219g	219g	220g	196g	

* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm