

## Rear Derailleurs MTB

Model No.	RDM97 LD	RDM91 LD	RDM57 LD	RDM41 LD	RDM37 LD	RDM37 LB	RDM37 SD	RDM37 SB	RDM36 SD	RDM36 SB
Cage Type	(L) Long	(L) Long	(L) Long	(L) Long	(L) Long	(L) Long	(S) Short	(S) Short	(S) Short	(S) Short
Mounting Type	(D) Direct	(D) Direct	(D) Direct	(D) Direct	(D) Direct	(B) Bracket	(D) Direct	(B) Bracket	(D) Direct	(B) Bracket
Speeds	9-Speed	9-Speed	8 / 7-Speed	8 / 7-Speed	7-Speed		7-Speed		6-Speed	
Max. Sprocket	34T	34T	34T	34T	30T		30T		30T	
Min. Sprocket	11T	11T	11T	11T	13T		13T		13T	
Rear Capacity	23T	23T	23T	23T	17T		17T		16T	
Max. Front Difference	22T	22T	20T	20T	20T		20T		20T	
Total Capacity	45T	45T	43T	43T	37T		37T		36T	
Outer Link	Aluminum	Steel	Steel	Steel	Engineering Polymers		Engineering Polymers		Engineering Polymers	
Inner Link	Steel	Steel	Steel	Steel	Steel		Steel		Steel	
Bracket Body	Aluminum	Aluminum	Engineering Polymers	Engineering Polymers	Engineering Polymers		Engineering Polymers		Engineering Polymers	
Plate Body	Aluminum	Engineering Polymers	Engineering Polymers	Engineering Polymers	Engineering Polymers		Engineering Polymers		Engineering Polymers	
Outer Plate Cage	Steel	Steel	Steel	Steel	Engineering Polymers		Engineering Polymers		Engineering Polymers	
Inner Plate Cage	Steel	Steel	Steel	Steel	Engineering Polymers		Engineering Polymers		Engineering Polymers	
Guide Pulley	11T (Bushing)	11T (Bushing)	11T(bushing)	11T(bushing)	11T		11T		11T	
Tension Pulley	11T (Bushing)	11T (Bushing)	11T(bushing)	13T(bushing)	11T		11T		11T	
Bracket Bolt	Steel	Steel	Steel	Steel	Steel		Steel		Steel	
Cable Adjuster	Composite	Composite	Composite	Composite	Composite		Composite		Composite	
Pin Bushing (Outer Link)	•	×	×	×	×		×		×	
Pin Bushing (Inner Link)	×	×	×	×	×		×		×	
Average Weight	335g	342g	354g	376g	230g	270g	225g	265g	225g	265g

## Rear Derailleurs MTB

Model No.	RDM2T LD	RDM2T LB	RDM2T SD	RDM2T SB	RDM15 LD	RDM15 LB	RDM15 SD	RDM15 SB	RDM10 LD	RDM10 LB
Cage Type	(L) Long	(L) Long	(S) Short	(S) Short	(L) Long	(L) Long	(S) Short	(S) Short	(L) Long	(L) Long
Mounting Type	(D) Direct	(B) Bracket	(D) Direct	(B) Bracket	(D) Direct	(B) Bracket	(D) Direct	(B) Bracket	(D) Direct	(B) Bracket
Speeds	7 / 6-Speed		7 / 6-Speed		5-Speed		5-Speed		Friction	
Max. Sprocket	28T		28T		28T		28T		28T	
Min. Sprocket	13T		13T		14T		14T		13T	
Rear Capacity	15T		15T		14T		14T		15T	
Max. Front Difference	20T		12T		20T		12T		20T	
Total Capacity	35T		27T		34T		26T		35T	
Outer Link	Steel		Steel		Steel		Steel		Steel	
Inner Link	Steel		Steel		Steel		Steel		Steel	
Bracket Body	Steel		Steel		Steel		Steel		Steel	
Plate Body	Steel		Steel		Steel		Steel		Steel	
Outer Plate Cage	Steel		Steel		Steel		Steel		Steel	
Inner Plate Cage	Steel		Steel		Steel		Steel		Steel	
Guide Pulley	10T		10T		10T		10T		10T	
Tension Pulley	10T		10T		10T		10T		10T	
Cable Adjuster	Composite		Composite		Composite		Composite		Steel	
Average Weight	265g	290g	251g	276g	265g	290g	253g	278g	265g	290g