

## Trigger Shifters

Model No.	DLMZ33	DLMZ33N	DLMZ33I
	RW	RW	RW
Side and Speed	Right 12-Spd	Right 12-Spd	Right 12-Spd
Gear Display	Podium Top	×	×
I-SPEC® II Compatible**	×	×	●
Shifting Operation	Push-Pull	Push-Pull	Push-Pull
Cable Adjuster	●	●	●
Multiple Shifts (Max.)	4	4	4
Clamp Screw	Stainless Steel	Stainless Steel	Stainless Steel
Large Lever	Aluminum	Aluminum	Aluminum
Small Lever	Engineering Polymers	Engineering Polymers	Engineering Polymers
Cable Type	Slick-Stainless	Slick-Stainless	Slick-Stainless
Cable Length	2,100mm	2,100mm	2,100mm
Casing Compatibility	SP	SP	SP
Finish	Black	Black	Black
Average Weight	139g	125g	123g

\* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

\*\*I-SPEC® is registered trademarks of Shimano, Inc.

Model No.	DLMX33			DLMX33N			DLMX33I		
	RE	L2	L3	RE	L2	L3	RE	L2	L3
Side and Speed	Right 11-Spd	Left 2-Spd	Left 3-Spd	Right 11-Spd	Left 2-Spd	Left 3-Spd	Right 11-Spd	Left 2-Spd	Left 3-Spd
Gear Display	Podium Top			×			×		
I-SPEC® II Compatible**	×			×			●		
Shifting Operation	Push-Pull			Push-Pull			Push-Pull		
Cable Adjuster	●			●			●		
Multiple Shifts (Max.)	4	1	1	4	1	1	4	1	1
Clamp Screw	Stainless Steel			Stainless Steel			Stainless Steel		
Large Lever	Aluminum			Aluminum			Aluminum		
Small Lever	Engineering Polymers			Engineering Polymers			Engineering Polymers		
Cable Type	Slick-Stainless			Slick-Stainless			Slick-Stainless		
Cable Length	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm
Casing Compatibility	SP			SP			SP		
Finish	Black			Black			Black		
Average Weight	139g	140g	140g	125g	126g	126g	123g	124g	124g

\* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

\*\*I-SPEC® is registered trademarks of Shimano, Inc.

## Trigger Shifters

Model No.	DLMS33			DLMS33N			DLMS33I			DLMS13		
	RT	L2	L3	RT	L2	L3	RT	L2	L3	RT	L2	L3
Side and Speed	Right 10-Spd	Left 2-Spd	Left 3-Spd	Right 10-Spd	Left 2-Spd	Left 3-Spd	Right 10-Spd	Left 2-Spd	Left 3-Spd	Right 10-Spd	Left 2-Spd	Left 3-Spd
Gear Display	Podium Top			×			×			Podium Top		
I-SPEC® II Compatible**	×			×			●			×		
Shifting Operation	Push-Pull			Push-Pull			Push-Pull			Push-Pull		
Cable Adjuster	●			●			●			●		
Multiple Shifts (Max.)	4	1	1	4	1	1	4	1	1	4	1	1
Clamp Screw	Stainless Steel			Stainless Steel			Stainless Steel			SCM435 Chromoly		
Large Lever	Aluminum			Aluminum			Aluminum			Engineering Polymers		
Small Lever	Engineering Polymers			Engineering Polymers			Engineering Polymers			Engineering Polymers		
Cable Type	Slick-Stainless			Slick-Stainless			Slick-Stainless			Slick-Galvanized		
Cable Length	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm
Casing Compatibility	SP			SP			SP			SP		
Finish	Black			Black			Black			Black		
Average Weight	139g	140g	140g	125g	126g	126g	123g	124g	124g	143g	144g	144g

\* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

\*\*I-SPEC® is registered trademarks of Shimano, Inc.

Model No.	DLM933			DLM903			DLM503		DLM403		
	R9	L2	L3	R9	L2	L3	R8	L3	R8	R7	L3
Side and Speed	Right 9-Spd	Left 2-Spd	Left 3-Spd	Right 9-Spd	Left 2-Spd	Left 3-Spd	Right 8-Spd	Left 3-Spd	Right 8-Spd	Right 7-Spd	Left 3-Spd
Gear Display	Podium Top			Podium Top			Podium Top		Podium Top		
I-SPEC® II Compatible**	×			×			×		×		
Shifting Operation	Push-Pull			Push-Pull			Push-Pull		Push-Pull		
Cable Adjuster	●			●			●		●		
Multiple Shifts (Max.)	6	1	1	6	1	1	5	1	5	5	1
Clamp Screw	Stainless Steel			SCM435 Chromoly			SCM435 Chromoly		SCM435 Chromoly		
Large Lever	Aluminum			Engineering Polymers			Aluminum		Engineering Polymers		
Small Lever	Engineering Polymers			Engineering Polymers			Engineering Polymers		Engineering Polymers		
Cable Type	Slick-Stainless			Slick-Galvanized			Slick-Galvanized		Slick-Galvanized		
Cable Length	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	1,700mm	2,100mm	1,700mm	2,100mm	2,100mm	1,700mm
Casing Compatibility	SP			SP			SP		SP	2SP & ↑	2SP & ↑
Finish	Black			Black			Black		Black		
Average Weight	139g	140g	140g	143g	144g	144g	144g	141g	143g	143g	144g

\* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

\*\*I-SPEC® is registered trademarks of Shimano, Inc.

## Trigger Shifters

Model No.	DLM90		DLM33			
	R9	L3	R8	R7	R6	L3
Side and Speed	Right 9-Spd	Left 3-Spd	Right 8-Spd	Right 7-Spd	Right 6-Spd	Left 3-Spd
Gear Display	Podium Top		Podium Top			
I-SPEC® II Compatible**	✕		✕			
Shifting Operation	Push-Push		Push-Push			
Cable Adjuster	●		●			
Multiple Shifts (Max.)	6	1	6	5	4	1
Clamp Screw	SUS302 Stainless Steel		SCM435 Chromoly			
Large Lever	Engineering Polymers		Engineering Polymers			
Small Lever	Engineering Polymers		Engineering Polymers			
Cable Type	Slick-Galvanized		Galvanized			
Cable Length	2,050mm	1,600mm	2,050mm			1,600mm
Casing Compatibility	SP		SP	2SP & ↑	2SP & ↑	2SP & ↑
Finish	Black		Black			
Average Weight	158g	157g	158g	158g	158g	157g

\* Handlebar diameter 22.2 ±0.2 mm / Tighten torque 60 ~ 80 kgf-cm

\*\*I-SPEC® is registered trademarks of Shimano, Inc.